DEKTOGAL Toolgal Dekton SOLUTIONS







After a year of development, Toolgal is proud to present the new line for cutting and drilling hard engineered materials as Dekton, Neolith and Lapitec.

All products are running successfully in the domestic market and in the US and demand is increasing continually.

DEKTOGAL saw blades and drill bits are characterized by its smooth and fine edges and accurate cut.

ITEM#	DESCRIPTION	DIAM. Mm.	THICKN. mm.
AP200707	D350 H60/50 DEKTOGAL - SILENT STEEL CORE	350	3
AP200702	D400 H60/50 DEKTOGAL - SILENT STEEL CORE	400	3.2

CUTTING PARAMETERS:

- Peripheral speed: 32-35m/sec.
- In Diam. 350mm. Approx. 1500-1700RPM.
- In Diam. 400mm. Approx. 1700-1900RPM.
- Recommended Cutting advance speed: 0.5-0.6m/min.
- Recommended advance speed in Cutting 45°: 0.4-0.5m/min.

DEKTON CNC/MANUAL CORE DRILL PART No. DIAMETER (mm) USEFUL LENGTH (mm) CONNECTION 1/2" BSP + M14				
PART No.	DIAMETER (mm)	USEFUL LENGTH (mm)		
RR002753	6	40		
RR002733	8	40		
RR002727	10	40		
RR002726	12	40		
RR002734	13	40		
RR002735	15	40		
RR002723	20	40		
RR002724	25	40		
RR002725	35	40		
RR002736	40	40		
RR002737	45	40		
RR002738	50	40		
RR002739	55	40		
RR002740	60	40		
RR002741	80	40		



CUTTING PARAMETERS:

- Rotational speed:
 - Approx. 4000RPM.
- Recommended drilling advance speed: 8.0-12m/min.



Toolgal Industrial Diamonds Ltd. Degania A' 1512000 Israel Tel: +972 4 6608445/6 Fax: +972 4 6752620 E-mail: toolgal@toolgal.com | www.toolgal.com

